

Multiple wire drawing machines Bul Blok

One passage wire-drawing machine

Mod. T1-1D



Dimensioni

Lung.	1300
Larg.	1200
Alt.	1300(2100)
Peso circa	850
Pot.	3

Caratteristiche

The wire drawing machine of the Bul Blok family are machines built for drawing both ogive tube and for the first drawing of the large wire, whether it comes directly from the rolling mill or from the continuous casting furnace.

Machine for drawing with maximum input diameter 12 mm, drawing power stress not more than 13000 Newton.

Driving coiler diameter 1000 mm.

Machine with electronic variation of drawing speed from 0 to 20 Mt/1' minute.

Forced lubrication on the die with decantation and recirculation system and with separate tank.

Construction standards in accordance to "CE" with respective documentation.

- Installed horse power 3 KW.

- Power supply 400V. 50HZ Three - Phase.

Accessori

- Winding coil diam. 250 mm
- Revolving protection on the work surface with safety micro-switch. (in accordance to CE)
- Pressuring roller in plastic material for containing the thread, with pneumatic drive.
- Input wire-guide with adjustable rollers 0-10 mm.
- Frictioned unwinding disc diameter 1000 mm with lateral containing.
- Net filter for refrigerant liquid

TVN TECH S.r.l. - MACCHINE PER ORAFI / MACHINERY FOR GOLDSMITHS

Via XXV Aprile n. 72 - 52048 Monte San Savino (Arezzo) Italy
 Tel. (0575) 810157 - 849149 - Fax (0575) 849149 - E-mail: info@tvntech.it - www.tvntech.it
 Cod.Fisc., P.Iva e Reg.Imp. AR IT 02191740519 - R.E.A. 168488
 Capitale sociale € 10.000,00 I.V.

Trafile multiple Bul Blok

Trafila a un passaggio Mod. T1-1D



Dimensioni

Lung.	1300
Larg.	1200
Alt.	1300(2100)
Peso circa	850
Pot.	3

Caratteristiche

La macchina è adatta alla trafilatura del tubo ad ogiva flottante e per la sgrossatura del filo di grandi dimensioni, proveniente direttamente dal laminatoio oppure dal forno a colata continua

Macchina adatta a trafilare con diametro max entrata 12 mm, con sforzi non superiori a 13000N

Diametro aspo trascinamento 1000 mm.

La macchina dispone di variazione elettronica della velocità di trafilatura da 0 a 20 Mt./min.

Lubrificazione sulla filiera con decantazione e ricircolo con serbatoio separato.

Costruzione secondo normative "CE" con relativa documentazione

- Potenza installata KW 3,

- Alimentazione 400V. 50HZ. Trifase.

Accessori

- Aspo di riavvolgimento diam.250 mm.
- Protezione basculante sul piano di lavoro con micro interruttore di sicurezza. (Versione ce)
- Rullo di pressione in materiale plastico per contenimento del filo, con azionamento pneumatico.
- Guidafile in entrata con rulli regolabili 0-10mm.
- Disco devolgitore frizionato diametro 1000mm con contenimento laterale.
- Filtro a rete per liquido refrigerante.

TVN TECH S.r.l. - MACCHINE PER ORAFI / MACHINERY FOR GOLDSMITHS

Via XXV Aprile n. 72 - 52048 Monte San Savino (Arezzo) Italy
 Tel. (0575) 810157 - 849149 - Fax (0575) 849149 - E-mail: info@tvntech.it - www.tvntech.it
 Cod.Fisc., P.Iva e Reg.Imp. AR IT 02191740519 - R.E.A. 168488
 Capitale sociale € 10.000,00 I.V.